

GPVP-35 series

35W Single Output Switching Power Supply with PFC Function



■ Features:

- Constant voltage design
- Built-in active PFC function, PFC > 0.9
- Universal AC input / Full range
- Protections: Short circuit / Overcurrent
- Cooling by free air convection
- 100% full load burn-in test
- Isolation class II
- Fully encapsulated with IP67 level



ELECTRICAL SPECIFICATION

MODEL	GPVP-35-12	GPVP-35-24
OUTPUT		
DC VOLTAGE	12V	24V
RATED CURRENT	3A	1.5A
CURRENT RANGE	0 ÷ 3A	0 ÷ 1.5A
RATED POWER	36W	
LINE REGULATION	± 1%	
LOAD REGULATION	± 2%	
VOLTAGE TOLERANCE [3]	± 5%	
RIPPLE & NOISE (max.) [2]	5V _{p-p}	5V _{p-p}
SETUP, RISE TIME [4]	2000ms, 250ms / 230VAC; 3000ms, 250ms / 115VAC at full load	
INPUT		
VOLTAGE RANGE	90 ÷ 264VAC	
FREQUENCY RANGE	47 ÷ 63Hz	
EFFICIENCY (typ.)	82%	84%
AC CURRENT (typ.)	0.6A/115VAC, 0.3A / 230VAC	
POWER FACTOR	PF > 0.9 / 230VAC; PF > 0.95 / 115VAC	
INRUSH CURRENT (typ.)	65A / 230VAC	
LEAKAGE CURRENT(max.)	1mA / 240VAC	
PROTECTIONS		
OVERCURRENT	Range: 110 ÷ 130% Type: constant current limiting, auto-recovery.	
SHORT CIRCUIT	Type: hiccup mode, auto-recovery.	

GPVP-35 series

35W Single Output Switching Power Supply with PFC Function



ENVIRONMENT

WORKING TEMPERATURE	-30°C ÷ 70°C (Refer to Derating Curve)
WORKING HUMIDITY	20 ÷ 90% RH non-condensing
STORAGE TEMPERATURE AND HUMIDITY	-40°C ÷ 80°C, 10 ÷ 95% RH non-condensing
TEMPERATURE COEFFICIENT	± 0.03% / °C (0°C ÷ 50°C)
VIBRATION	10 ÷ 500Hz, 2G, 10min / cycle, period for 60min. each along X, Y, Z axes

SAFETY & EMC REGULATIONS


SAFETY STANDARDS	Compliance to EN61347-1, EN61347-2-13, IP67
WITHSTAND VOLTAGE	I-P/O-P: 3kVAC
ISOLATION RESISTANCE	I-P/O-P; O-P/FG; I-P/FG: 100MΩ/500VDC/25°C/70%
EMC EMISSION	Compliance to EN55015
EMC IMMUNITY	Compliance to EN61547; EN55024; EN61000-4-2, -3, -4, -5, -6, -8, -11
HARMONIC CURRENT	Compliance to EN61000-3-3; EN61000-3-2 class C (≥ 60% load)

OTHERS

DIMENSIONS	149 x 32 x 28mm
WEIGHT AND PACKING	0.23kg; 80pcs./box; box weight and dimensions: 19kg; 34.5 x 24 x 26cm

1. All parameters NOT specially mentioned are measured at 230VAC input, rated load and 25°C of ambient temperature.
2. Ripple & noise are measured at 20MHz of bandwidth by using a 12" twisted pair-wire terminated with a 0.1μF i 47μF parallel capacitor.
3. Tolerance includes set up tolerance, line regulation and load regulation.
4. Setup and rise time is measured from 0 to 90% rated output voltage.
5. Power supply is considered as a component that will be operated in combination with final equipment. Since EMC performance will be affected by the complete installation, the final equipment must be re-qualified to comply with EMC Directives.

MECHANICAL SPECIFICATION



DERATING CURVE

