



The IP40 protected decorative enclosures are available in sizes from 8 to 72M. They provide superior aesthetic integration and are equipped with screw wiring multipolar terminal blocks, 80 A IP 20. They are available with smoked transparent doors or with blank doors that can be equipped with safety lock, characterized by the "PUSH" opening and closing. The terminal blocks allow to create simple and neat wiring reducing the set-up time of the enclosure.


|                                      |   |                           |  |
|--------------------------------------|---|---------------------------|--|
| Insulation class                     | II (according to IEC 61140 standards)                     | Colour                    | White RAL 9016                               |
| Outer dim. LxHxD (mm)                | 400x400x130   | IP degree                 | IP40   |
| Dispersible power (W)                | 45  | Mechanical resistance     | IK08   |
| Rated voltage                        | 400 V   | Door colour               | Blank  |
| Terminal blocks                      | 80 A - IP20 bipolar holes with screws                     | No. of modules EN 50022   | 36 (18x2)                                    |
| Rated current                        | 125 A   | Glow Wire Test            | 650 °C                                       |
| Operating temperature                | -25 +60 °C  | Type of material          | Halogen-free in compliance with EN 60754-2   |
| Electrocod                           | 0321  | Thermo-pressure with ball | 70 °C  |
| Accessories for insulation restoring | Screwcaps (GW44623) or fixing brackets in resin (GW44621) | Standard                  | EN 60670-1 (CEI 23-48) IEC60670-24 CEI 23-49 |
| Insulation voltage                   | 750 V   | Pole 1 (mm <sup>2</sup> ) | N/E (3x16) + (17x10)                         |
| Pole 2 (mm <sup>2</sup> )            | N/E (3x16) + (17x10)                                      |                           |  |

#### BEHAVIOUR WITH CHEMICAL AND ATMOSPHERIC AGENTS

| Saline solution | Acids         |                    | Bases         |                    | Solvents           |               |               |                    | Mineral oil        | UV rays            |
|-----------------|---------------|--------------------|---------------|--------------------|--------------------|---------------|---------------|--------------------|--------------------|--------------------|
|                 | Concentrated  | Diluted            | Concentrated  | Diluted            | Hexane             | Benzol        | Acetone       | Alcohol            |                    |                    |
| Resistant       | Not resistant | Limited resistance | Not resistant | Limited resistance | Limited resistance | Not resistant | Not resistant | Limited resistance | Limited resistance | Limited resistance |

#### DIMENSIONAL



#### TECHNICAL SYMBOLOGY



**IP**  
IP40

**IK**  
IK08

**GWT**  
650 °C



#### STANDARDS/APPROVALS



GEWISS S.p.A. Via A. Volta, 1  
24069 Cenate Sotto - Bergamo - Italy  
tel. +39 035 94 61 11 fax +39 035 94 69 09

www.gewiss.com  
sat@gewiss.com  
Last update 12/05/2020

changed at any moment, therefore it is always recommended to read the last updated version published on the website [www.gewiss.com](http://www.gewiss.com). Lumen output and system power are subject to a tolerance of +/- 10%. Unless stated otherwise, the values apply to an ambient temperature of 25°C. Terms of warranty at <https://www.gewiss.com/it/en/company/landingpage/led-warranty>.